

- B7
Cont
- synthetic silicone alternate. 0.1%
 - glassene silicone alternate 0.99%
 - plasticiser agent 0.5%
 - polyester waxing agent $1.23\% \pm 0.3\%$
 - emulsifier $2.0\% + 0.6\%$ --
-

In the Claims:

Replace Claim 4 as follows

B2

-- 4. (Twice Amended) A composite label including a first layer for displaying information at a first major surface of the label, and a second layer including a removable portion arranged so as to be separated from the label and secured to another object, wherein the second layer includes an adhesive on one side thereof for securing the removable portion to the first later and the first layer includes a release coating to facilitate removal of the portion therefrom, the adhesive and release coating providing a release strength factor of between 17 grams force / 50 mm and 30 grams force / 50 mm, and wherein the first layer is formed of polyester and the second layer includes material having a density less than the polyester. --

Add the following new Claims 19 and 20:

B2

-- 19. (New) A composite label as claimed in claim 1, wherein the second layer is formed of a material having a softness less than polyester, to allow the second layer to be cut or scored so as to define the removable portion, without compromising the integrity of the first layer.---

-- 20. (New) A composite label as claimed in claim 4, wherein the second layer is formed of a material having a softness less than polyester, to allow the second layer to be cut or scored so as to define the removable portion, without compromising the integrity of the first layer.--

B3
Carl